

# **Previous Yamaha LAN Monitor** **version information**

## **V1.3.3**

### **New Features**

- Now supports managing the following L2 switch
  - SWR2311P-10G

### **Notice**

- This application will not operate unless at least one SWP1 series unit exists on the same network as the computer. Only one computer can run this application on the same network.
- This application will not run via a wireless LAN. A wired Ethernet connection is required.
- For details on this application, refer to "Yamaha LAN Monitor User Guide."

## **V1.2.6**

### **New Features**

- The software name of Yamaha Audio Network Monitor has been changed to Yamaha LAN Monitor.
- Now supports managing the following switches.
  - SWR2100P-5G
  - SWR2100P-10G
- "Dante Discovery" and "Dante Controller and Monitoring" can be selected and installed by the installer.
- Now supports Windows 8.1

### **Improvements**

- History messages are now saved as log.
- Fixed a problem in which the application might be suspended if you enter an IP address of L2MS slave (switch) up to second octet then confirm.

## **V1.2.0**

- Solved a problem in which some devices could not be recognized as Dante devices.
- Solved a problem in which, when executing an overwrite install of Yamaha Audio Network Monitor, the system attempted to uninstall Dante Infrastructure.

## **V1.1.0**

- Now supports Windows 10.
- Updated the database to be used in the automatic identification function of company name by MAC address.

## **V1.0.1**

- The initial release version.

### **Notice**

- This application will not operate unless at least one SWP1 series unit exists on the same network as the computer. Only one computer can run this application on the same network.
- This application will not run via a wireless LAN. A wired Ethernet connection is required.
- For details on this application, refer to "Yamaha Audio Network Monitor User Guide."